

DIASTAR Ten Pneumatically Actuated Zero Static Valve

PROGEF® Natural PP

Main Size [mm]	Branch Size [mm]	Valve Size [mm]	Zero Static - Fail Safe to Close (FC)	
			IR/Butt Fusion	
			EPDM	PTFE/EPDM
20	20	20	168 629 101	168 629 301
25	20	25	168 629 103	168 629 303
25	25	25	168 629 104	168 629 304
32	20	25	168 629 107	168 629 307
32	25	25	168 629 108	168 629 308
32	32	32	168 629 109	168 629 309
40	20	32	168 629 112	168 629 312
50	20	25	168 629 118	168 629 318
50	25	32	168 629 119	168 629 319
50	32	32	168 629 120	168 629 320
63	20	25	168 629 125	168 629 325
63	25	32	168 629 126	168 629 326
63	32	32	168 629 127	168 629 327



The DIASTAR Ten is rated for 10 bar combined pressure

DIASTAR TenPlus Pneumatically Actuated Zero Static Valve

PROGEF® Standard PP

Main Size [mm]	Branch Size [mm]	Valve Size [mm]	Zero Static - Fail Safe to Close (FC)	
			IR/Butt Fusion	
			EPDM	PTFE/EPDM
20	20	20	167 689 101	167 689 301
25	20	25	167 689 103	167 689 303
25	25	25	167 689 104	167 689 304
32	20	25	167 689 107	167 689 307
32	25	25	167 689 108	167 689 308
32	32	32	167 689 109	167 689 309
40	20	32	167 689 112	167 689 312
50	20	25	167 689 118	167 689 318
50	25	32	167 689 119	167 689 319
50	32	32	167 689 120	167 689 320
63	20	25	167 689 125	167 689 325
63	25	32	167 689 126	167 689 326
63	32	32	167 689 127	167 689 327



The DIASTAR TenPlus is rated for 10 bar bidirectional pressure

DIASTAR TenPlus Pneumatically Actuated Zero Static Valve

SYGEF® Plus PVDF

Main Size [mm]	Branch Size [mm]	Valve Size [mm]	Zero Static - Fail Safe to Close (FC)	
			IR/Butt Fusion	
			PTFE/EPDM	PTFE/FPM
20	20	20	181 689 301	181 689 501
25	20	25	181 689 303	181 689 503
25	25	25	181 689 304	181 689 504
32	20	25	181 689 307	181 689 507
32	25	25	181 689 308	181 689 508
32	32	32	181 689 309	181 689 509
40	20	32	181 689 312	181 689 512
40	25	32	181 689 313	181 689 513
40	32	32	181 689 314	181 689 514
40	40	32	181 689 315	181 689 515
50	20	25	181 689 318	181 689 518
50	25	32	181 689 319	181 689 519
50	32	32	181 689 320	181 689 520
50	40	63	181 689 321	181 689 521
50	50	63	181 689 322	181 689 522
63	20	25	181 689 325	181 689 525
63	25	32	181 689 326	181 689 526
63	32	32	181 689 327	181 689 527
63	40	63	181 689 328	181 689 528
63	50	63	181 689 329	181 689 529
63	63	63	181 689 330	181 689 530
90	20	32	181 689 341	181 689 541
90	25	32	181 689 342	181 689 542
90	32	32	181 689 343	181 689 543
90	50	63	181 689 345	181 689 545
90	63	63	181 689 346	181 689 546
110	20	32	181 689 351	181 689 551
110	25	32	181 689 352	181 689 552
110	32	32	181 689 353	181 689 553
110	50	63	181 689 355	181 689 555
110	63	63	181 689 356	181 689 556



The DIASTAR TenPlus is rated for 10 bar bidirectional pressure