

Type 240 Pneumatically Actuated Wafer Butterfly Valve

PVC

| d - Size [mm]-[inch] | Fail Safe to Close (FC) | | Fail Safe to Open (FO) | |
|-------------------------|-------------------------|-------------|------------------------|-------------|
| | EPDM | FPM | EPDM | FPM |
| 63 - 2 | 199 240 002 | 199 240 022 | 199 240 042 | 199 240 062 |
| 75 - 2 ½ | 199 240 003 | 199 240 023 | 199 240 043 | 199 240 063 |
| 90 - 3 | 199 240 004 | 199 240 024 | 199 240 044 | 199 240 064 |
| 110 - 4 | 199 240 005 | 199 240 025 | 199 240 045 | 199 240 065 |
| 140 - 5 | 199 240 006 | 199 240 026 | 199 240 046 | 199 240 066 |
| 160 - 6 | 199 240 007 | 199 240 027 | 199 240 047 | 199 240 067 |
| 225 - 8 | 199 240 008 | 199 240 028 | 199 240 048 | 199 240 068 |
| 280 - 10 | 199 240 009 | 199 240 029 | 199 240 049 | 199 240 069 |
| 315 - 12 | 199 240 010 | 199 240 030 | 199 240 050 | 199 240 070 |

| d - Size [mm]-[inch] | Double Acting (DA) | |
|-------------------------|--------------------|-------------|
| | EPDM | FPM |
| 63 - 2 | 199 240 082 | 199 240 102 |
| 75 - 2 ½ | 199 240 083 | 199 240 103 |
| 90 - 3 | 199 240 084 | 199 240 104 |
| 110 - 4 | 199 240 085 | 199 240 105 |
| 140 - 5 | 199 240 086 | 199 240 106 |
| 160 - 6 | 199 240 087 | 199 240 107 |
| 225 - 8 | 199 240 088 | 199 240 108 |
| 280 - 10 | 199 240 089 | 199 240 109 |
| 315 - 12 | 199 240 090 | 199 240 110 |



CPVC

| d - Size [mm]-[inch] | Fail Safe to Close (FC) | | |
|-------------------------|-------------------------|-------------|-------------|
| | EPDM | FPM | PTFE/FPM |
| 63 - 2 | 199 240 162 | 199 240 182 | 199 240 642 |
| 75 - 2 ½ | 199 240 163 | 199 240 183 | 199 240 643 |
| 90 - 3 | 199 240 164 | 199 240 184 | 199 240 644 |
| 110 - 4 | 199 240 165 | 199 240 185 | 199 240 645 |
| 140 - 5 | 199 240 166 | 199 240 186 | 199 240 646 |
| 160 - 6 | 199 240 167 | 199 240 187 | 199 240 647 |
| 225 - 8 | 199 240 168 | 199 240 188 | 199 240 648 |
| 280 - 10 | 150 240 169 | 150 240 189 | - |
| 315 - 12 | 150 240 170 | 150 240 190 | - |

| d - Size [mm]-[inch] | Fail Safe to Open (FO) | | |
|-------------------------|------------------------|-------------|-------------|
| | EPDM | FPM | PTFE/FPM |
| 63 - 2 | 199 240 202 | 199 240 222 | 199 240 662 |
| 75 - 2 ½ | 199 240 203 | 199 240 223 | 199 240 663 |
| 90 - 3 | 199 240 204 | 199 240 224 | 199 240 664 |
| 110 - 4 | 199 240 205 | 199 240 225 | 199 240 665 |
| 140 - 5 | 199 240 206 | 199 240 226 | 199 240 666 |
| 160 - 6 | 199 240 207 | 199 240 227 | 199 240 667 |
| 225 - 8 | 199 240 208 | 199 240 228 | 199 240 668 |
| 280 - 10 | 150 240 209 | 150 240 229 | - |
| 315 - 12 | 150 240 210 | 150 240 230 | - |



Type 240 Pneumatically Actuated Wafer Butterfly Valve

CPVC

| d - Size [mm]-[inch] | Double Acting (DA) | | |
|-------------------------|--------------------|-------------|-------------|
| | EPDM | FPM | PTFE/FPM |
| 63 - 2 | 199 240 242 | 199 240 262 | 199 240 682 |
| 75 - 2 ½ | 199 240 243 | 199 240 263 | 199 240 683 |
| 90 - 3 | 199 240 244 | 199 240 264 | 199 240 684 |
| 110 - 4 | 199 240 245 | 199 240 265 | 199 240 685 |
| 140 - 5 | 199 240 246 | 199 240 266 | 199 240 686 |
| 160 - 6 | 199 240 247 | 199 240 267 | 199 240 687 |
| 225 - 8 | 199 240 248 | 199 240 268 | 199 240 688 |
| 280 - 10 | 150 240 249 | 150 240 269 | - |
| 315 - 12 | 150 240 250 | 150 240 270 | - |



PROGEF® Standard PP

| d - Size [mm]-[inch] | Fail Safe to Close (FC) | | |
|-------------------------|-------------------------|-------------|-------------|
| | EPDM | FPM | PTFE/FPM |
| 63 - 2 | 199 240 282 | 199 240 302 | 199 240 702 |
| 75 - 2 ½ | 199 240 283 | 199 240 303 | 199 240 703 |
| 90 - 3 | 199 240 284 | 199 240 304 | 199 240 704 |
| 110 - 4 | 199 240 285 | 199 240 305 | 199 240 705 |
| 140 - 5 | 199 240 286 | 199 240 306 | 199 240 706 |
| 160 - 6 | 199 240 287 | 199 240 307 | 199 240 707 |
| 225 - 8 | 199 240 288 | 199 240 308 | 199 240 708 |
| 280 - 10 | 199 240 289 | 199 240 309 | 199 240 709 |
| 315 - 12 | 199 240 290 | 199 240 310 | 199 240 710 |

| d - Size [mm]-[inch] | Fail Safe to Open (FO) | | |
|-------------------------|------------------------|-------------|-------------|
| | EPDM | FPM | PTFE/FPM |
| 63 - 2 | 199 240 322 | 199 240 342 | 199 240 722 |
| 75 - 2 ½ | 199 240 323 | 199 240 343 | 199 240 723 |
| 90 - 3 | 199 240 324 | 199 240 344 | 199 240 724 |
| 110 - 4 | 199 240 325 | 199 240 345 | 199 240 725 |
| 140 - 5 | 199 240 326 | 199 240 346 | 199 240 726 |
| 160 - 6 | 199 240 327 | 199 240 347 | 199 240 727 |
| 225 - 8 | 199 240 328 | 199 240 348 | 199 240 728 |
| 280 - 10 | 199 240 329 | 199 240 349 | 199 240 729 |
| 315 - 12 | 199 240 330 | 199 240 350 | 199 240 730 |



Type 240 Pneumatically Actuated Wafer Butterfly Valve

PROGEF® Standard PP

| d - Size [mm]-[inch] | Double Acting (DA) | | |
|-------------------------|--------------------|-------------|-------------|
| | EPDM | FPM | PTFE/FPM |
| 63 - 2 | 199 240 362 | 199 240 382 | 199 240 742 |
| 75 - 2 ½ | 199 240 363 | 199 240 383 | 199 240 743 |
| 90 - 3 | 199 240 364 | 199 240 384 | 199 240 744 |
| 110 - 4 | 199 240 365 | 199 240 385 | 199 240 745 |
| 140 - 5 | 199 240 366 | 199 240 386 | 199 240 746 |
| 160 - 6 | 199 240 367 | 199 240 387 | 199 240 747 |
| 225 - 8 | 199 240 368 | 199 240 388 | 199 240 748 |
| 280 - 10 | 199 240 369 | 199 240 389 | 199 240 749 |
| 315 - 12 | 199 240 370 | 199 240 390 | 199 240 750 |
| 355 - 14 | 199 240 371 | 199 240 391 | - |
| 400 - 16 | 199 240 372 | 199 240 392 | - |
| 450 - 18 | 199 240 373 | 199 240 393 | - |
| 500 - 20 | 199 240 374 | 199 240 394 | - |
| 630 - 24 | 199 240 375 | 199 240 395 | - |



ABS

| d - Size [mm]-[inch] | EPDM | | |
|-------------------------|-------------------------|------------------------|--------------------|
| | Fail Safe to Close [FC] | Fail Safe to Open [FO] | Double Acting [DA] |
| 63 - 2 | 199 240 402 | 199 240 422 | 199 240 442 |
| 75 - 2 ½ | 199 240 403 | 199 240 423 | 199 240 443 |
| 90 - 3 | 199 240 404 | 199 240 424 | 199 240 444 |
| 110 - 4 | 199 240 405 | 199 240 425 | 199 240 445 |
| 140 - 5 | 199 240 406 | 199 240 426 | 199 240 446 |
| 160 - 6 | 199 240 407 | 199 240 427 | 199 240 447 |
| 225 - 8 | 199 240 408 | 199 240 428 | 199 240 448 |
| 280 - 10 | 199 240 409 | - | - |
| 315 - 12 | 199 240 410 | - | - |



Type 240 Pneumatically Actuated Wafer Butterfly Valve

SYGEF® Standard PVDF

| d - Size [mm]-[inch] | Fail Safe to Close (FC) | | Fail Safe to Open (FO) | |
|-------------------------|-------------------------|-------------|------------------------|-------------|
| | FPM | PTFE/FPM | FPM | PTFE/FPM |
| 63 - 2 | 199 240 462 | 199 240 522 | 199 240 482 | 199 240 542 |
| 75 - 2 ½ | 199 240 463 | 199 240 523 | 199 240 483 | 199 240 543 |
| 90 - 3 | 199 240 464 | 199 240 524 | 199 240 484 | 199 240 544 |
| 110 - 4 | 199 240 465 | 199 240 525 | 199 240 485 | 199 240 545 |
| 140 - 5 | 199 240 466 | 199 240 526 | 199 240 486 | 199 240 546 |
| 160 - 6 | 199 240 467 | 199 240 527 | 199 240 487 | 199 240 547 |
| 225 - 8 | 199 240 468 | 199 240 528 | 199 240 488 | 199 240 548 |
| 280 - 10 | 199 240 469 | 199 240 529 | 199 240 489 | 199 240 549 |
| 315 - 12 | 199 240 470 | 199 240 530 | 199 240 490 | 199 240 550 |
| d - Size [mm]-[inch] | Double Acting (DA) | | | |
| | FPM | PTFE/FPM | | |
| 63 - 2 | 199 240 502 | 199 240 562 | | |
| 75 - 2 ½ | 199 240 503 | 199 240 563 | | |
| 90 - 3 | 199 240 504 | 199 240 564 | | |
| 110 - 4 | 199 240 505 | 199 240 565 | | |
| 140 - 5 | 199 240 506 | 199 240 566 | | |
| 160 - 6 | 199 240 507 | 199 240 567 | | |
| 225 - 8 | 199 240 508 | 199 240 568 | | |
| 280 - 10 | 199 240 509 | 199 240 569 | | |
| 315 - 12 | 199 240 510 | 199 240 570 | | |

